

DTLC-3000 BRINELL

In a situation where low to medium Brinell testing is required, the DTLC-3000 is the smart choice. Measuring test forces by using an enclosed load cell, this Brinell tester provides accurate and efficient tests every time. With its stylish cast-iron enclosure and affordable price, you'll find the DTLC-3000 to be the perfect fit for your shop or laboratory.

Special Features

- 10 selectable loads to choose from
- Direct load method with load-cell feedback
- Automatic applying, holding and removing of loads
- Selectable dwell times
- User-friendly touch-pad panel
- Certified and ready to use

| ITEM | DTLC-3000 |
|-------------------------|--|
| LOADS | 62.5, 187.5, 250, 500, 750, 1000, 1500, 2000, 2500, 3000 kgf |
| DWELL TIME | 5 to 60 seconds |
| MAXIMUM SPECIMEN HEIGHT | 9.5" (241.3mm) |
| MAXIMUM SPECIMEN DEPTH | 5" (127mm) |
| LED DISPLAY | 4-Digit Kg display |
| ACCURACY | Conforms to ASTM-E-10 |
| DIMENSIONS | 7.5" x 21" x 28" (190x533x711mm) |
| WEIGHT | Apix. 285 lbs |
| POWER SUPPLY | 115 VAC 60 Hz |

STANDARD ACCESSORIES

| | | |
|---|-------------|---|
| Hardness Standard | | 1 |
| 10mm Carbide Ball Indenter | | 1 |
| Flat Anvil | 2.5" (60mm) | 1 |
| Flat Anvil | 8" (200mm) | 1 |
| V-Anvil | 2.5" (60mm) | 1 |
| Machine Cover, Conversion Chart, Manual | | |

Appearance and specifications are subject to change without prior notice.

